

### KERN HTS Industrial crane scale up to 10 t, IP65, with EC-Type Approval (M)

**Delivery**  
7 days

**3 Years warranty**

**FACTORY OPTION**

**M Verification**

**DKD Certificate +3 days**

#### Further functions

- 10 tare memory units
- 10 unassigned memory units, e.g. for weight increments or identification numbers
- Totals memory, adds up all individual weighing processes (TOTAL)
- Peak load display (manual peak hold)

#### Charge condition indicator

for integrated rechargeable battery pack, using LED

#### Display Gross/Tare/Net

by means of LEDs

#### Luminescent LED display

digit height 30 mm. The luminosity can be adjusted in 2 stages to preserve the battery. Digit height for models with  
**Max** ≤ 1.500 kg: 25 mm  
**Max** ≥ 3.000 kg: 30 mm

#### Data hold function

the weight display is "frozen" by double-pressing a key, until the "C" key is pressed

#### Infrared remote control

standard. Range approx. 15 m. All functions can be selected. Input via numeric key pad, incl. protective case, WxDxH 200x80x28 mm



STANDARD



robust metal housing

#### Standby function

automatic switch off of the display after 5 min without a change of load. Automatic activation with the touch of a key

#### Rechargeable battery pack

internal, standard, operating time approx. 150 h, charging time approx. 15 h. For models with **Max** ≤ 1.500 kg internal with mains adapter. Can be reordered, **KERN HTS-A01**

For models with **Max** ≥ 3.000 kg external, through battery charger. Can be reordered, **KERN HTS-A02**


**Technical Data:**  
Precision 0.1% of **Max**

**UNITS** Further weighing units (only HTS without "M"): see the internet.



#### Verifiable version

Please indicate at purchase: desired model with M add-on, e.g. HTS 600K200 IPM. Order example:  
**Scale price**  
 + Add. price, verifiability  
 Total scale price  
 + Verification (if required)



**Ready for use**  
Battery size AA (2x 1.5V) included

**Hook**  
with safety catch, revolving

**I** For applications that require verification, please order verification at the same time, initial verification at a later date is not possible.

Model	Weigh. range Max kg	Read-out d g	Min. load Min kg	Net weight approx. kg	Housing size WxDxH mm	Dimensions				Verifi- cation KERN	OPTIONS alternative	
						A	B	C	D		M III	Certifi- cate KERN
KERN HTS 150K50IP	150	50	1	14	200x204x160	45	30	435	480	950-129	963-129	
HTS 300K100IP	300	100	2	14	200x204x160	45	30	435	480	950-129	963-129	
HTS 600K200IP	600	200	4	14	200x204x160	45	30	435	480	950-130	963-130	
HTS 1.5T0.5IP	1500	500	10	14	200x204x160	60	28	443	505	950-130	963-130	
HTS 3T1IP	3000	1000	20	40	279x254x381	90	45	735	815	950-132	-	
HTS 6T2IP	6000	2000	40	65	279x254x381	100	67	900	1040	950-132	-	
HTS 10T5IP	10000	5000	100	65	279x254x381	100	67	900	1040	950-132	-	

104

Order Hotline: Go to back page of catalogue

### KERN - Your DKD-Calibration Partner

issues DKD calibration certificates for balances and test weights in its own accredited laboratories. It is internationally valid.

KERN is a manufacturer of test weights in the international classes of accuracy

**E1, E2, F1, F2, M1, M2, M3, from 1 mg up to 2000 kg**

**DKD = German Calibration Service**



Your KERN specialist dealer